



PARROT SYSTEM PAR 4-20 mA



The Marchwood PAR 4-20 mA is a “one to one” wireless cable replacement system consisting of a paired transmitter and receiver.

It is designed to remove the requirement of installing expensive cable and cable containment.

The transmitter and receiver are designed to fit on a standard DIN rail.

The Modules are based on the Texas Instruments CC430F5137 System-on-Chip device to provide an intelligent radio sub-system that combines a high performance RF transceiver, RF band pass filters (BPF), an MSP430 microcontroller, 32Kb flash memory, non-volatile flash storage, temperature sensor, and a low drop voltage regulator. 10 bit resolution giving better than 0.5% accuracy.

The device operates on the International licence exempt Industrial, Scientific and Medical (ISM) radio bands.

System has a 500 metre range and low power operation. Range can be extended to 10,000 metres with external antennas.

FEATURES

- Clips onto standard DIN rail
- Monitored for power and Tx/Rx failure
- Easy view LEDs for operational status
- Tx is loop powered, isolated and no polarized.
- AES 120 bit data encryption
- Modules requires a nominal 24vDC supply
- RX and TX can be fitted with external antennas



MODULES

- Dispatched as a paired set of modules, transmitter and receiver
- 4-20 pairs are calibrated and ready to use

CERTIFICATION

- ISM Frequency Bands 433 & 868MHz (UK & Europe) & 915MHz (USA)
- Radio Compliance: ETSI RED (Europe) & FCC Certified (USA) IC (Canada) requirements
- UKCA compliant
- CE marked
- Power Supply



OPTIONS

- SMA connection for external antenna



ADDRESS :

Marchwood Technologies Ltd.
Unit 1, 28 Black Moor Road,
Ebblake Industrial Estate,
Verwood, BH31 6BB
United Kingdom

EMAIL :

Sales@Marchwood.co.uk
www.marchwood.co.uk

PHONE :

+44 (0)1202 810770